



Product Information Sheet



Sheet Number: **0064**

Rev 22-11-06

ROOFBOND Rustshield W

Acrylic water based anti- rust roof sealer

Rustshield W is an acrylic anti-rust sealer/ primer designed to penetrate and prime in preparation for Roofbond roof coatings to follow. Rustshield W is airless sprayed using a 517 tip and is single pac coloured grey.

General Application Guide: Spray 1 coat of Rust Shield W with airless spray gun and a 517-521 tip after cleaning and repair steps listed in the Roofbond application sheet.

Suitable for Colorbond®, Zinalume® and Rusty Galvanised Sheeting.



Specifications:

(dry times are considered at 25°)

Roofbond Rustshield W :

Surface Dry: 1/2-2 hours

Top Coat: 2-4 hours

Hard Dry: 3 -5 days

Wet Film Thickness: 120 microns

Dry Film Thickness: 60 microns

Thinning: No thinning required normally. If desired thin with water sparingly.

Clean Up: Clean up with water



Top Picture: Rustshield W being sprayed over Galvanised metal roofing.

Bottom Picture: Spraying Roofbond roof paint .

Rustshield W comes in 15 litre pails.

See MSDS for safety information

Features:

Anti- Rust Primer

Grey Colour

Flexible

Easy To Apply

Promotes Adherence

Pre Mixed

Binds Chalkiness of surface

Benefits:

Eliminates Rust

Dries a grey colour

Allows for some substrate move-

Airless Sprayed

Job flows with ease

Stirring only required

Paint adheres well

Notes: There are many substrates on the market. Please consult Shieldcoat for further information regarding applications not on this sheet.