



Product Information Sheet



Sheet Number: **0062**

Rev 22-11-06

ROOFBOND Shieldseal W Plus

Acrylic water based roof sealer

Shieldseal W Plus is an acrylic sealer designed to penetrate and prime in preparation for Roofbond roof coatings to follow. Shieldseal W Plus is airless sprayed using a 517 tip and dries clear.

General Application Guide: Spray 1 coat of Shieldseal W Plus with airless spray gun after cleaning and repair steps listed in the Roofbond application sheet.

Suitable for Colorbond®, Zinalume® and Fibre Cement Sheeting.



Specifications:

(dry times are considered at 25°)

Roofbond Shieldseal W Plus:

Surface Dry: 1/2-2 hours

Top Coat: 2-4 hours

Hard Dry: 3 -5 days

Wet Film Thickness: N/A

Dry Film Thickness: N/A

Thinning: No thinning required normally. If desired thin with water sparingly.

Clean Up: Clean up with water



Top Picture: Shieldseal W Plus being sprayed over ColorBond® metal roofing.

Bottom Picture: Spraying Roofbond roof paint over Shieldseal W Plus.

Primer Plus comes in 15 litre pails.

See **MSDS** for safety information

Features:

- Penetrating Primer
- Clear Colour
- Flexible
- Easy To Apply
- Promotes Adherence
- Pre Mixed
- Binds Chalkiness of surface

Benefits:

- Good Adhesion
- Dries clear
- Allows for some substrate move-
- Airless Sprayed
- Job flows with ease
- Stirring only required
- Paint adheres well

Notes: There are many substrates on the market. Please consult Shieldcoat for further information regarding applications not on this sheet.