

meyBATTEN

LVL ROOF BATTEN



meyBATTEN
LVL ROOF BATTEN

SIZE: 65 x 35
LENGTH: 5.7m
TOLERANCE: +/-2mm
TREATMENT: H2-S to AS/NZS 1604.1
COATING: Red Moisture Barrier

- ◉ **STRAIGHT, LONG LENGTHS**
- ◉ **PREDICTABLE PERFORMANCE**
- ◉ **H2-S PROTECTED AGAINST TERMITES**
- ◉ **MOISTURE BARRIER TO MINIMISE BATTEN DISTORTION**

meyBATTEN is available as a 65 x 35 in 5.7m lengths specifically designed for use as roof battens. **meyBATTEN** will be straighter, less prone to breaking, and have reduced tendency to split at connections. **meyBATTEN** has a genuine moisture barrier to reduce timber distortion whilst exposed to outdoor construction conditions. The inclusion of a glueline protection against termites provides added security.

meyBATTEN Span Table

Wind Classification	Max Truss/Rafter Spacing (mm)	Max Roof Batten Spacing (mm) <i>General & within 1.2m of edge</i>	Max Roof Batten Spacing (mm) <i>Within 1.2m of eaves corner</i>
N1, N2	900	1200	
N3		1200	1000
N4		1000	700

NOTES: 1. Roof battens designed for sheet roof only (<25kg/m²). 2. Roof battens to be continuous over minimum 2 spans.

Meyer
TIMBER

Meyer
TIMBER
Victoria

Meyer
TIMBER
New South Wales

Meyer
TIMBER
Queensland

Meyer
TIMBER
Tasmania

www.meyertimber.com.au

AVAILABLE THROUGH:

