



**VELUX®**

# World-Leading Skylights

April 2025 Product Information & Price List

Skylights, Sun Tunnels, Roof Windows & Accessories




# Contents

- 4** Pitched Roof Skylights
  - FS** Fixed Skylight
  - VS** Manual Skylight
  - VSE** Electric Skylight
  - VSS** Solar skylight
  
- 8** Flat Roof Skylights
  - FCM** Fixed Skylight
  - VCM** Manual Skylight
  - VCS** Solar skylight
  
- 12** Roof Windows
  - GGL** Center-Pivot
  - GPL** Dual Action
  
- 14** Sun Tunnels
  - TWF** Flexible (Tiled Roof)
  - TWR** Rigid (Tiled Roof)
  - TCR** Rigid (Flat Roof)
  
- 16** Blinds
  - Honeycomb Blackout
  - Pleated Translucent
  
- 18** Flashing
  - VELUX Single Unit Flashing
  - VELUX Combination Flashing
  - Custom Flashing
  
- 20** Light Shafts
  
- 21** Accessories
  - Manual Controls
  - Electric Controls
  - VELUX ACTIVE
  
- 22** Price List and Sizes



Transforming Spaces







## Pitched Roof Skylights



Designed to bring daylight and fresh air into any room, our pitched roof skylights are ideal for pitched roofs over 15° and can be easily installed on tile roof using the VELUX EDW flashing kits, or custom flashed to suit a wide variety of metal roofs.

Crafted with a durable timber frame, they combine strength, style, and performance—helping to transform your home with the beauty of natural light.



FIXED SKYLIGHT (FS)	MANUAL SKYLIGHT (VS)	ELECTRIC SKYLIGHT (VSE)	SOLAR SKYLIGHT (VSS)
✓	✓	✓	✓
<b>NATURAL LIGHT:</b> Contributes toward NCC (building code) regulations requiring natural light			
✓	✓	✓	✓
<b>MADE FOR AUSTRALIA:</b> Tested to guarantee reliability and to meets all relevant Australian standards			
✓	✓	✓	✓
<b>DESIGN FLEXIBILITY:</b> Without vertical windows, walls can be utilised for storage, decoration, or appliances, and have added privacy			
✓	✓	✓	✓
<b>VENTILATION:</b> Contributes toward NCC (building code) regulations requiring ventilation			
✓	✓	✓	✓
<b>REDUCED A/C:</b> Reduce the need to install A/C units by building homes that naturally ventilate rising heat			
✓	✓	✓	✓
<b>REDUCE MOISTURE:</b> Ventilate in kitchens to remove steam, or bathrooms for ventilation with privacy			
✓	✓	✓	✓
<b>REMOTE OPERATED:</b> Skylight is operated by RF wall-mounted keypad with a range of approx. 10m. Multiple skylights can be operated from 1 keypad			
✓	✓	✓	✓
<b>RAIN SENSOR:</b> Skylight automatically closes when rain is detected for peace of mind (included)			
✓	✓	✓	✓
<b>USES STANDARD GPO:</b> No hard wiring, plugs into standard GPO located in roof cavity (2m cable provided)			
✓	✓	✓	✓
<b>SOLAR POWERED:</b> Solar panel charges a concealed battery, allowing operation day or night and doesn't require an electrician to install			
✓	✓	✓	✓
<b>BATTERY POWER BANK:</b> Concealed battery pack charges during the day, providing up to 100 uses when fully charged			
✓	✓	✓	✓
<b>NO ELECTRICIAN REQUIRED:</b> Low voltage cables can be safely handled by anyone (does not come with power plug)			

Blinds - details on page 16 & 17	FS	VS, VSE, VSS
Honeycomb Blackout	FSCD	FSCH
Pleated Translucent	FSLD	FSLH

### Installation Information (refer to page 18)

#### Guarantee Information

10 Years - Skylight, glazing, frame, manual operators, flashing and coverings  
3 Years - Blinds & electronic components

#### Package inclusions

**VS** - Insect screen, operator (manual), and operating eyelet (manual controls purchased separately)  
**VSE** - Insect screen, operator (electric), wall mounted keypad, rain sensor  
**VSS** - Insect screen, operator (solar), battery pack, wall mounted keypad, rain sensor, solar panel



## BUILDING CODE REGULATIONS & TECHNICAL PERFORMANCE

### U VALUE

	 FIXED SKYLIGHT (FS)	 MANUAL SKYLIGHT (VS)	 ELECTRIC SKYLIGHT (VSE)	 SOLAR SKYLIGHT (VSS)
--	---	--	---	--

Skylight: 2.6 Glass: 1.93	Skylight: 2.5 Glass: 1.93	Skylight: 2.5 Glass: 1.93	Skylight: 2.5 Glass: 1.93
------------------------------	------------------------------	------------------------------	------------------------------

### SHGC (Solar Heat Gain Co-efficient)

Skylight: 0.24 Glass: 0.28	Skylight: 0.21 Glass: 0.28	Skylight: 0.21 Glass: 0.28	Skylight: 0.21 Glass: 0.28
-------------------------------	-------------------------------	-------------------------------	-------------------------------

### UV PROTECTION

99% Reduction of harmful UV spectrum (UVA & UVB)

✓	✓	✓	✓
---	---	---	---

### BUSHFIRE (AS3959)

BAL 40

\*Custom-made flashing required. Skylight tested in closed position, metal flywire mesh protection required for opening apertures (consult local council). Roof pitch; 18°-75°

✓	✓	✓	✓
---	---	---	---

### HAIL TEST

VELUX Simulated Tests ASTM E822-2009

\*Hailstone test not performed on solar panel. Solar panel not attached during test.

✓	✓	✓	✓
---	---	---	---

### Window Energy Rating Scheme (WERS)

Maximum 5-star summer rating

✓	✓	✓	✓
---	---	---	---

### SKYLIGHT STANDARD (AS4285)

✓	✓	✓	✓
---	---	---	---

### OVERHEAD GLAZING (AS1288)

Laminated glass (standard) must be used for skylights installed 3m or more above floor level.

✓	✓	✓	✓
---	---	---	---

### WIND LOADS - NON-CYCLONIC REGIONS (AS4055)

✓	✓	✓	✓
---	---	---	---

### BOUNDARY SEPARATION

Class 1 and Class 10 buildings: Within 900mm of a boundary wall

Class 2 to Class 9 buildings: 3 metres from a boundary wall

\*CSIRO assessment report available on request. VELUX recommends consultation with relevant authority for possible Performance Solution before work commences. Skylight assessed in closed position.

✓	✓	✓	✓
---	---	---	---



HAIL TESTED



BUSHFIRE BAL40



WIND LOADS



### Blinds - details on page 16 & 17

Honeycomb Blackout

Pleated Translucent

FS VS, VSE, VSS

FSCD

FSLD

FSCH

FSLH

## ACCESSORIES (Sold Separately)

### Manual Controls (VS only)

In-reach -Winder handle: ZZZ 201

Just out of reach - Short control rod (60cm): ZOZ 032

Out of reach - Extension Rod (up to 285cm): ZCT 300

(See page 21 for more information)

### Electric Controls (VSE/VSS only)

Wall Mounted Keypad KLI 310 (Included with VSE/VSS)

**VELUX ACTIVE** KIX 300

Indoor climate control system


**Smart Home Interface Unit:** KLF 200

Building management system interface

Read more about our electric control solutions on page 21.

## GLAZING

High Performance Double Glazing





## Flat Roof Skylights



VELUX flat roof skylights are designed to provide flat roofs with a versatile and high-performance skylight, enabling the transformation of home extensions and other spaces with flat roofs when used in combination with custom flashing.

The curb mounted construction makes them an ideal upgrade when replacing aging plastic dome skylights, as they fit onto the same flashing base while providing hail resistance and the superior insulation of double glazing.



Fixed Skylight (FCM)	Manual Skylight (VCM)	Solar Skylight (VCS)
<b>NATURAL LIGHT:</b> Contributes toward NCC (building code) regulations requiring natural light		
✓	✓	✓
<b>DESIGN FLEXIBILITY:</b> Without vertical windows, walls can be utilised for storage, decoration, or appliances, and have added privacy		
✓	✓	✓
<b>SKYLIGHT REPLACEMENT:</b> Perfect double glazed product to replace old plastic dome skylights.		
✓	✓	✓
<b>VENTILATION:</b> Contributes toward NCC (building code) regulations requiring ventilation		
	✓	✓
<b>REDUCED A/C:</b> Reduce the need to install A/C units by building homes that naturally ventilate rising heat		
	✓	✓
<b>REDUCE MOISTURE:</b> Ventilate in kitchens to remove steam, or bathrooms for ventilation with privacy		
	✓	✓
<b>REMOTE OPERATED:</b> Skylight is operated by RF wall-mounted keypad with a range of approx. 10m.		
		✓
<b>RAIN SENSOR:</b> Skylight automatically closes when rain is detected by the externally mounted rain sensor (included)		
		✓
<b>BATTERY POWER BANK:</b> Concealed battery pack charges during the day, providing up to 100 uses when fully charged		
		✓
<b>SOLAR POWERED:</b> Solar panel charges a concealed battery, allowing operation day or night and doesn't require an electrician to install		
		✓
<b>NO ELECTRICIAN REQUIRED:</b> Low voltage cables can be safely handled by anyone		
		✓

Blinds - details on page 16 & 17	FCM	VCM, VCS
Honeycomb Blackout	FSCC + ZZZ 199 Tray*	FSCC

\*Requires ZZZ 199 tray

Installation Information (refer to page 18)

Guarantee Information

10 Years - Skylight, glazing, frame, manual operators, coverings  
3 Years - Blinds & electronic components

Package inclusions

**VCM** - Insect screen, operator (manual), and operating eyelet (manual controls purchased separately)  
**VCS** - Insect screen, operator (solar), battery pack, wall mounted keypad, rain sensor, solar panel



## BUILDING CODE REGULATIONS/TECHNICAL PERFORMANCE

### U VALUE



### SHGC (SOLAR HEAT GAIN CO-EFFICIENT)

### UV PROTECTION

99% Reduction of harmful UV spectrum (UVA & UVB)

### BUSHFIRE (AS3959)

BAL 40

\*Custom-made flashing required. Skylight tested in closed position, metal flywire mesh protection required for opening apertures (consult local council). Roof pitch; 0-60°.

### HAIL TEST

VELUX Simulated Tests ASTM E822-2009

\*Hailstone test not performed on solar panel. Solar panel not attached during test.

### Window Energy Rating Scheme (WERS)

Maximum 5-star summer rating

### SKYLIGHT STANDARD (AS4285)

\*Cyclone test not performed with screws provided, installation requires #8 roofing screws.

### OVERHEAD GLAZING (AS1288)

### WIND LOADS - NON-CYCLONIC REGIONS (AS4055)

### NT DTCM PRESSURE RATINGS

\*Skylight must be installed in accordance with the engineering drawings, contact VELUX for more information.

### BOUNDARY SEPARATION

Class 1 and Class 10 buildings: Within 900mm of a boundary wall

Class 2 to Class 9 buildings: 3 metres from a boundary wall

\*CSIRO assessment report available on request. VELUX recommends consultation with relevant authority for possible Performance Solution before work commences. Skylight assessed in closed position



HAIL TESTED



BUSHFIRE BAL40



WIND LOADS



CODEMARK®  
Australia  
30090

## Blinds - details on page 16 & 17

Honeycomb Blackout

FCM

FSCC + ZZZ 199  
Tray\*

VCM, VCS

FSCC

\*Requires ZZZ 199 tray

## ACCESSORIES (Sold Separately)

### Manual Controls (VCM only)

In-reach -Winder handle: ZZZ 212

Just out of reach - Short control rod (60cm): ZOZ 032

Out of reach - Extension Rod (up to 285cm): ZCT 300

(See page 21 for more information)

### Electric Controls (VCS only)

Wall Mounted Keypad KLI 310 (Included with VCS)

**VELUX ACTIVE** KIX 300

Indoor climate control system


**Smart Home Interface Unit:** KLF 200

Building management system interface

Read more about our manual and electric control solutions on page 21.

## GLAZING

High Performance Double Glazing  
Standard across entire skylight range



FCM 4646 & FCM 4672 outer pane is 3.9mm.



## Roof Windows



15°-55°  
INSTALLATION PITCH

Specifically designed for use in attic spaces, our roof windows turn underutilized areas into an extra bedroom, retreat or home office. The opening mechanisms have been built to allow quick and easy use within reach, adding both natural light and ventilation to otherwise dark spaces. Roof windows help you maximize your home's potential, allowing your attic to become a functional extension of your living space.



GGL	GPL
<b>NATURAL LIGHT:</b> Contributes toward NCC (building code) regulations requiring natural light	
✓	✓
<b>CLEAN FROM INSIDE:</b> Can be rotated 180 and locked in place for cleaning the outer pane from inside.	
✓	✓
<b>VENTILATION:</b> Contributes toward NCC (building code) regulations requiring ventilation	
✓	✓
<b>DUAL OPENING:</b> The GPL can be opened both in center pivot motion and in top hung awning style.	
	✓
<b>USABLE ATTIC SPACE:</b> Being top hung, the sash opens outwards, providing more functional attic space	
	✓
<b>OPTIONAL INSECT SCREEN:</b> Insect screens are available for purchase for the GPL, keeping out flies and mosquitoes	
	✓

BUILDING CODE REGULATIONS/TECHNICAL PERFORMANCE	GGL	GPL
<b>CODEMARK</b>	✓	✓
<b>U VALUE</b>		Roof Window: 1.3 Glass: 1.0
<b>SHGC (SOLAR HEAT GAIN CO-EFFICIENT)</b>		Roof Window: 0.31 Glass: 0.30
<b>UV PROTECTION</b> 99% Reduction of harmful UV spectrum (UVA & UVB)	✓	✓
<b>SKYLIGHT STANDARD (AS4285)</b> *Except cyclonic wind pressure (GPL only)	✓	✓
<b>OVERHEAD GLAZING (AS1288)</b>	✓	✓
<b>BOUNDARY SEPARATION</b> Class 1 and Class 10 buildings: Within 900mm of a boundary wall Class 2 to Class 9 buildings: 3 metres from a boundary wall *CSIRO assessment report available on request. VELUX recommends consultation with relevant authority for possible Performance Solution before work commences. Skylight assessed in closed position	✓	✓
<b>Blinds - details on page 16 &amp; 17</b>	GGL	GPL
Manual Honeycomb Blackout	FHC	FHC
Insect Screen *ZIL Insect Screen is fitted to ceiling to cover plaster reveal. Suitable for within-reach applications only. NB: side channel length to be cut to size.		ZIL

Installation Information (refer to page 18)

Guarantee Information

10 Years Roof window, glazing, frame, manual operators, flashing and coverings



## Sun Tunnels

When a traditional skylight isn't an option, sun tunnels offer the perfect alternative. Designed for tight spaces like walk-in robes, pantries, and powder rooms, they provide natural light to spaces where a traditional skylight wouldn't fit or when the roof cavity has obstructions. With minimal structural changes required, they are a quick and cost-effective way to brighten dark areas when you don't want to rely on artificial lighting.



### SUITABLE FOR ROOFING TYPE

PRODUCT	TWF	TWR	TCR- <b>NEW</b>
Suitable for roof material	Tiled Roof	Tiled Roof	Metal Roof
Suitable for roof pitches	15-60°	15-60°	0-60°
Tunnel diameter - 350mm	✓	✓	✓
Highly reflective shaft provides up to 3x as much light compared to TWF		✓	✓
Flexible tunnel allows installation even when obstructions in the roof cavity exist	✓		



### CEILING DIFFUSER

#### EASY TO CLEAN

Threaded diffuser screws on and off allowing for easy removal for cleaning.

#### EDGE GLOW

A clear ring on the diffuser's circumference throws light further.

### BUILDING CODE REGULATIONS/TECHNICAL PERFORMANCE

	TWF	TWR	TCR
<b>CODEMARK</b>	Yes	Yes	TBC
<b>U VALUE</b>	2.4	2.4	TBC
<b>SHGC</b>	0.5	0.61	TBC
<b>BUSHFIRE (AS3959)</b>	N/A	BAL 29 Roof pitch; 18°-60°	N/A
<b>SKYLIGHT STANDARD (AS4285)</b>	Yes *Except Cyclonic Wind Pressure	Yes *Except Cyclonic Wind Pressure	TBC

#### Installation Information (refer to page 18)

TCR requires custom flashing.

#### Guarantee Information

7 Years

#### Package inclusions

**TWF** - Integrated flashing, 2200mm flexible tunnel, ceiling diffuser

**TWR** - Integrated flashing, 1600mm rigid tunnel including 2x 45° 'elbows', ceiling diffuser

**TCR** - 1150mm rigid tunnel including 2x 45° 'elbows', ceiling diffuser





**PERFECT FIT**  
Designed for seamless integration with VELUX skylights.



**SOLAR POWERED**  
VELUX offers a range of solar powered blinds for most products.




**EASY OPERATION**  
Open with the press of a button with keypad provided.

### Honeycomb Blackout - Ultimate Light Control & Insulation

For those who want superior thermal comfort and light blocking.

- Double-layered fabric for superior insulation – Keeps your home cooler in summer and warmer in winter.
- Room darkening effect – Ideal for bedrooms and media rooms.
- Modern, sleek design – Neatly retracts for a clean look when not in use.

*Best for: Bedrooms, Home Offices, Media Rooms*



### Pleated Translucent – Soft Light & Privacy

For those who love diffused or softer natural light.

- Gently diffuses daylight – Reduces glare while maintaining a bright, airy feel.
- Flexible light control – Adjustable to any position on the skylight.
- Elegant fabric texture – Adds softness and warmth to any room.

*Best for: Living Rooms, Kitchens & Bathrooms*



Blind	Light Reduction	Heat Reduction
Honeycomb Blackout	98%	70%
Pleated Translucent	40%	27%

## Blinds Make the Difference

No window is complete without a blind and the same is true of skylights. VELUX blinds are tailored to perfectly fit VELUX skylights, giving you control at your fingertips.

Whether you're looking for a solution to soften natural light or provide total blackout, our range of blinds provides the ideal solution. Choose from our Honeycomb or Pleated Translucent blinds to complete your skylight installation.

BLIND OPTIONS	FS	VS, VSE, VSS	FCM	VCM, VCS	GGL, GPL
Manual Honeycomb Blackout					FHC
Solar Honeycomb Blackout	FSCD	FSCH	FSCC + ZZZ 199 Tray*	FSCC	
Solar Pleated Translucent	FSLD	FSLH			

\*Requires ZZZ 199 tray to install blind

Additional colours available upon request. Contact VELUX for more information.





## Custom Flashing

### GENERAL PRINCIPLES TO A 4 PIECE FLASHING


- 1 Length of flashing should extend at least 250mm below the skylight
- 2 Upstand height should be a minimum of 100mm
- 3 Flashing width should cover at least 2 ribs of your roofing material
- 4 Where possible, dry pan the flashing to the ridge line
- 5 For best results, add a thin line of silicone between flashing overlaps
- 6 Add diverters on each corner to direct water away from flashing joints
- 7 Add turn downs and cut outs to flashing edges to provide a tight seal against roofing material

### FLAT ROOF SKYLIGHTS CONSIDERATIONS


Flat roof skylights are designed with a curb for seamless integration with custom-made dry-pan flashings, even on flat roofs. The curb mounted design offers a high degree of flexibility, making them suitable for all metal roofing profiles.

Although there are several ways to build the hob, VELUX recommends a timber hob for greater thermal performance and structural support (particularly for cyclonic zones).

4 Piece Flashing




Flat Roof Skylight Installation Method



### PITCHED ROOF SKYLIGHT CONSIDERATIONS

Although VELUX supplies flashing for pitched roof skylights, you may be required to custom flash in some situations such as in BAL zones, or may choose to do so, such as when colour matching to the roof.

*Additional top shroud for header flashing needed for pitched roof skylights*



## VELUX Flashing EDW

VELUX offers a range of flashing kits designed to integrate your skylights perfectly into your roofing material, ensuring the skylight is completely weathertight no matter the weather conditions.

EDW Flashing is designed to direct water through the aluminium side channels and over the apron which is designed to be molded to the shape of your tiles for a secure fit.

EDW Flashing can also be used on metal roofs that have a profile height less than 30mm, such as corrugated iron, however, custom flashing is another method often used on metal roofs. VELUX offers a range of EDL flashing suitable for slate roofs.

VELUX skylights can be coupled together using 'combi' flashing in a variety of configurations that allows you to design inspiring skylight features in your home.

**Contact VELUX for more information on combi flashing.**

# Light Shafts

## Why Getting it Right Matters

The internal lightshaft is one of the most crucial elements for your skylight installer to get right. It plays a major role in how the skylight will look and function. A well-designed lightshaft not only enhances the look of your skylight but also maximises the natural light from your skylight. When done correctly, it can transform a space, making it feel brighter, more open, and visually stunning.



### Splaying the Shaft

The angle and size of the lightshaft are key factors in determining how light enters the room. Splaying the shaft—angling the sides outward—creates a larger footprint on the ceiling. By creating a wider opening with the lightshaft you have a better view to the sky and maximise the amount of natural light entering the room.

### Refining the Finish

In cathedral ceilings, where exposed trusses are present, or bulkheads between multiple skylights, wrapping the timber with gyprock can enhance architectural elements rather than detract from them. A detailed and well-finished bulkhead or truss wrap ensures the skylight feels like an intentional design feature rather than an afterthought.

### Think Outside the Square

A lightshaft doesn't have to mirror the shape of the skylight itself. The internal shaft can be finished in a variety of creative shapes—circles, ovals, or even star-shaped designs. This flexibility allows homeowners and designers to turn the lightshaft into a unique architectural feature, showcasing the skylight in the best light.

# Accessories

## MANUAL ACCESSORIES

### Winder Handles

VS: ZZZ 201



VCM: ZZZ 212



### Extension Rods

Short Control Rod: ZOZ 032

60cm rod that attached to operating hook for use just out of reach.



Telescopic Rod: ZCT 300

Adjustable telescopic rod that can be extended between 145-285cm to operate VS/VCM skylights



## ELECTRONIC ACCESSORIES

### Interface Unit: KLF 200

Interface unit management systems and 3rd party switches. KLF 200 can be set up to perform 5 independent groups of products.



### Keypad: KLI 310

Radio frequency wall mounted keypad used to operate VELUX products. Comes with a wall mounting kit. Battery powered (AAA).



## VELUX ACTIVE

With VELUX ACTIVE, sensors continuously monitor the temperature, humidity and CO2 levels in your home and open or close your VELUX electric and solar powered products to create a healthier indoor climate. VELUX ACTIVE kit includes 1x Gateway, 1x Climate Sensor, 1x Departure Switch.



### Internet Gateway

The Gateway enables control of your VELUX products on your smart phone and connects your VELUX products, indoor climate sensor and departure switch. Takes inputs from local weather data, your smart phone, and sensors to control your VELUX products. Operates on 2.4Ghz, select the 2.4Ghz channel in dual mode on your modem.

### Climate Sensor

The indoor climate sensor continuously measures temperature, humidity and air quality (CO2 levels) in the room.

1 climate sensor is recommended per room with VELUX products; additional sensors can be purchased: KLA 300.

### Departure Switch

Tap the departure switch as you leave home if you want to turn the VELUX ACTIVE system off while you're out.

# Price List

Skylights and roof windows (does not apply to FCM models) can only be installed as per orientation depicted below.

FCM 2270/3072/4672 not recommended for landscape orientation.

## Pitched Roof Skylights



Overall frame dimension wxh mm		550x700	550x980	550x1180	550x1400	550x1800	780x780	780x1180	780x1180	780x1400	1140x700	1140x1180
<b>Skylights</b>	Size code	C01	C04	C06	C08	C12	M02	M04	M06	M08	S01	S06
FS (Fixed Skylight)	RRP \$	532	614	705	788	1114	725	765	866	969	843	1006
VS (Manual Skylight)	RRP \$	1228	1248	1334	1402	-	1402	1463	1597	1731	1540	1941
VSE (Electric Skylight)	RRP \$	2311	2339	2402	2461	-	-	2509	2618	2727	2595	2894
VSS (Solar Powered Skylight)	RRP \$	2492	2522	2590	2653	-	2643	2705	2822	2941	2798	3120

Blinds	Size code	C01	C04	C06	C08	C12	M02	M04	M06	M08	S01	S06
FSCD (Solar Honeycomb FS)	RRP \$	614	614	614	614	768	628	628	628	628	641	641
FSLD (Solar Pleated FS)	RRP \$	614	614	614	614	-	628	628	628	628	641	641
FSCH (Solar Honeycomb VS/VSE/VSS)	RRP \$	614	614	614	614	-	628	628	628	628	641	641
FSLH (Solar Pleated VS/VSE/VSS)	RRP \$	614	614	614	614	-	628	628	628	628	641	641

Flashing	Size code	C01	C04	C06	C08	C12	M02	M04	M06	M08	S01	S06
EDW (Tile/Metal Roof)	RRP \$	109	114	115	122	152	131	131	135	138	139	162

## Flat Roof Skylights



Overall curb dimension wxh mm		460x870	665x655	665x870	665x970	665x1275	665x1885	870x870	870x1275	870x1505	870x1935	970x970	970x1275	1275x665	1275x1275	1275x1935
<b>Skylights</b>	Size code	1430	2222	2230	2234	2246	2270	3030	3046	3055	3072	3434	3446	4622	4646	4672
FCM (Fixed Skylight)	RRP \$	351	381	414	438	497	896	481	611	745	1889	547	645	-	677	2102
VCM (Manual Skylight)	RRP \$	-	1296	-	1400	1547	-	1621	1760	-	-	1694	-	-	2064	-
VCS (Solar Skylight)	RRP \$	-	2510	-	2654	2828	-	2837	2976	-	-	2899	-	2846	3119	-

Blinds	Size code	1430	2222	2230	2234	2246	2270	3030	3046	3055	3072	3434	3446	4622	4646	4672
FSCC (Solar Honeycomb)	RRP \$	-	615	615	615	706	627	627	-	-	641	641	680	680	-	-

FCM Blind Trays*	Size code	1430	2222	2230	2234	2246	2270	3030	3046	3055	3072	3434	3446	4622	4646	4672
ZZZ 199	RRP \$	-	95	95	95	95	122	98	98	-	-	101	101	105	105	-

\*Requires ZZZ 199 tray to install blind to FCM

Refer to your VELUX distributor for shipping times.

## Roof Windows



Overall frame dimension wxh mm		550x780	550x980	780x980	780x1180	780x1400	1140x1180
<b>Roof Windows</b>	Size code	CK02	CK04	MK04	MK06	MK08	SK06
GGL (Centre Pivot Roof Window)	RRP \$	814	863	1010	-	1234	1528
GPL (Dual Action Roof Window)	RRP \$	-	969	1114	1221	1381	1608

Blinds	Size code	CK02	CK04	MK04	MK06	MK08	SK06
FHC (Manual Honeycomb)	RRP \$	247	265	273	292	318	342
ZIL (Insect Screen for GPL only)	RRP \$	-	339	419	419	419	465

Flashing	Size code	CK02	CK04	MK04	MK06	MK08	SK06
EDW (Roof Tile)	RRP \$	109	126	145	149	152	170

## Sun Tunnels

Product	RRP \$	
TWR OK14 (Rigid Sun Tunnel, Pitched Roof).	747	RRP \$
TWF OK14 (Flexible Sun Tunnel, Pitched Roof).	461	RRP \$
TCR OK14 (Rigid Sun Tunnel, Flat Roof).	795	RRP \$
ZTR 014 (Rigid Extension 1180mm - not suitable for TWF).	297	RRP \$

## Accessories

Product	Description	RRP \$	
ZZZ 201	Winder handle (white to operate VS opening skylights within reach).	57	RRP \$
ZZZ 212	Winder handle (white to operate VCM low pitch opening skylights within reach).	57	RRP \$
ZZZ 203	Eyelet with Universal Joint.	69	RRP \$
ZOZ 032	Short rod control (60 cm) to operate within reach.	70	RRP \$
ZCT 300	Extendable rod control to operate manual opening skylights, 145cm - 285cm length.	96	RRP \$
KIX 300	VELUX ACTIVE starter kit - includes 1 x internet gateway, 1 x climate sensor, 1 x departure switch.	709	RRP \$
KLA 300	VELUX ACTIVE Indoor climate sensor. Additional climate sensors required to extend your VELUX ACTIVE system to additional rooms.	317	RRP \$
KLF 200	Interfact Unit, Connect to third party building managements systems, sensors and switches.	741	RRP \$
KLR 300	Touchscreen remote to operate multiple products.	285	RRP \$



**VELUX®**

VELUX Australia Pty Ltd  
78 Henderson Road, Alexandria NSW 2015

1300 859 856  
customer.service@velux.com.au  
@veluxaustralia

[velux.com.au](https://www.velux.com.au)

The utmost care has been taken to provide accurate information. However, VELUX shall not be held responsible for any consequences arising from any errors or omissions in the catalogue nor for any damage or accidental loss resulting from the use of the information herein. VELUX reserves the right to modify, through development improvements, the products displayed in this brochure without notification.  
©2025 VELUX GROUP, VELUX®, VELUX logo, Made for Australia logo are registered trademarks. V-AUS 0325